

Nanoflex D 50

General

It is a fastness enhancing product.

Advantages

- Nanoflex D 50 increases all fastness of products which mixing it.
- Nanoflex D 50 provides extremely wash fastness. Suitable to ecological standards.

Applications

Nanoflex D 50 has been manufactured to obtain soft effected printings.

Usage

- Nanoflex D 50 is an discharge print paste.
- Recommended percentage : % 5 - 20

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between [+5]-[+30] °C/[+41]-[+86] °F of temperature.
- It should be consumed within 2 years after the production date.

Technical Details:

 **Appearance**
Paste

 **Odor**
Characteristic

 **Color**
Transparent

 **Viscosity**
.


 **Density**
1,0 g/cm³ [77 °F/25° C


 **Specific Gravity**
.

 **pH**
7.0-8.0

 **Boiling Point**
>100°C [212°F]

 **Solubility**
Soluble in water

 **Explosion Hazard**
It is not explosive

 **Packaging Information**
Nanoflex D 50 is packed in
1 / 5 /10 /20 / 30/ 60 kg plastic cans.

[Standarts: for fastness tests -
ISO 105-X10: 1993 / ISO 105-D01:2010 /
ISO 105-B02:2013]

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.